

BIOMETRIC TERMINAL SYSF203TP



Basic features

- 2,8" LCD Biometric Reader
- Three-dimensional face shape scanning
- Verification also using finger, card or code
- Support Emmarine 125 kHz cards
- Input/Output Wiegand 26/34 bit



FACIAL RECOGNITION



FINGERPRINT READER



EMMARINE CARDS READER



SPECIFICATIONS

Facial recognition	Facev4.0
Verification mode	Fingerprint/Card/Code
Display	2.8" LCD Touch Screen
Camera	2 x with IR lenses
Optic sensor	AES1711 500 dpi
FAR/FRR	0,01%, 1%
Face capacity	500
Fingerprint capacity	3 000
Card capacity	3 000
Event memory	500 000
Communications	TCP/IP, RS485, Wiegand
Software application	P2P SYSDO CLOUD System
Built-in relays	Door lock/ring
(Max. power loading)	1A/30V DC
Power supply	9 ~ 12V DC (1A)
Operation Temperature	-10 ~ 60 °C
Operation Humidity	20 ~ 80 %
Dimension	174 x 142 x 87 mm
Weight	460 g




TCP/IP
communication

Emmarine 125 kHz

Wiegand Input/Output

2,8" TFLCD Display

Two verification cameras



1. Power-In
2. GND
3. WGNOUT1
4. WGNOUT0
5. WGNIN1
6. WGNIN0



1. Lock-NC
2. Lock-COM
3. Lock-NO
4. Bell-NC
5. Bell-COM
6. Bell-NO
7. Door Sensor
8. Exit-in
9. GND



ON-LINE ATTENDANCE SYSTEM

The reader, in conjunction with the SYSDO portal, creates a comprehensive system of attendance and access. This will give you full control over the attendance of people anywhere in the world without the need to install software.

Try free demo at:
www.sysdo.cn

