

DS-K1T680DF-E1 Face Recognition Terminal



Face recognition terminal is a kind of access control device for face recognition, which is mainly applied in security access control systems, such as logistic centers, airports, university campuses, alarm centrals, dwellings, etc.

- 8-inch touch screen with bezel-less design
- Presents card on the screen to authenticate
- Face recognition distance: 0.3 m to 3 m, duration < 0.2 s/User, accuracy rate ≥ 99%
- 100,000 face capacity, 100,000 card capacity (Felica, DESfire, M1), 10,000 fingerprint capacity, and 150,000 event capacity
- Supports ISAPI, ISUP 5.0, Wiegand, RS-485, TCP/IP, and PoE
- Two-way audio with indoor station and main station
- Configuration via the web client and mobile client
- Customizes attendance status name

^{*}Biometric recognition products are not 100% applicable to anti-spoofing environments. If you require a higher security level, use multiple authentication modes.



Specification


Specification			
Display			
Screen size	8 inch		
Operation method	Capacitive touch screen		
Туре	LCD		
Video			
Lens	2		
Resolution	2 MP		
FOV	HFOV = 88°; VFOV = 44°; DFOV = 108°		
Network			
Wired network	Support		
Interface			
Network interface	1 RJ-45, 10/100/1000 M self-adaptive		
Lock control	1		
Exit button	1		
Door contact input	1		
Alarm input	2		
Alarm output	1		
TAMPER	1		
RS-485	1 RS-485 (Half duplex, HIKVISION)		
Wiegand	1 Wiegand(Hik 26bit,Hik 34bit)		
USB	1		
Authentication			
Card type	DESfire card,Felica card		
General			
Power supply	12 to 24 VDC, 3 A, Standard PoE		
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)		
Working humidity	0 to 90% (No condensing)		
Protective level	IP65		
Dimensions	127.3 mm × 232.1 mm × 23.5 mm (5.0" × 9.1" × 0.9")		
Function			
Hik-Connect	Support		
Language	English, Thai, Brazilian Portuguese, Russian, Spanish, Arabic, Japanese, Ukrainian, and		
	Indonesian		
QR code recognition	Support. The dimension of the recognized QR code picture should be larger than 6 cm		
QN COUR TECOSTILLOIT	× 6 cm.		
Face anti-spoofing	Support		

Available Model

DS-K1T680DF-E1

Dimension





Accessory

Optional

DS-KAB6-D1 Base Bracket	DS-KAB6-ZU1 Brackets for face terminals	DS-KAB671-P2 Stand Stick	DS-KAB6-W1 Bracket
1			

See Far, Go Further



www.hikvision.com support@hikvision.com















